



Electric Pumps

PE30, PE40, PE50 Series
- Single Phase

- Meets OSHA regulations for sound (80dBA).
- 2 Stage pumps provide fast run up before the high pressure stage.
- Suction strainers screen out contamination to prevent pump damage.
- All units are wired as 240 VAC 50 Hz.
- All hand pendants are wired 24 VAC for safety.
- Starts under full load.



PE40M4N02D



PEW03 Optional

Use with Cylinder Type	Flow Rate				Motor Size
	1 st Stage		2 nd Stage		
	L/min	BAR	L/min	BAR	

Manual Valve							
	3W/3P Advance /Hold Return		4.80	24.15	0.30	700	0.5 Hp
			5.10	48.30	0.61	700	1.0 Hp
			7.80	48.30	1.00	700	1.5 Hp
	4W/3P Advance /Hold/Return		6.3	48	1.22	700	3 Hp
			4.80	24.15	0.30	700	0.5 Hp
			5.10	48.30	0.61	700	1.0 Hp
			7.80	48.30	1.00	700	1.5 Hp
			6.3	48	1.22	700	3 Hp
Manual Valve w/3 meter Motor Pendant							
	3W/3P Advance /Hold Return		4.80	24.15	0.30	700	0.5 Hp
			5.10	48.30	0.61	700	1.0 Hp
			7.80	48.30	1.00	700	1.5 Hp
	4W/3P Advance /Hold/Return		6.3	48	1.22	700	3 Hp
			4.80	24.15	0.30	700	0.5 Hp
			5.10	48.30	0.61	700	1.0 Hp
			7.80	48.30	1.00	700	1.5 Hp
			6.3	48	1.22	700	3 Hp
Solenoid Valve w/3 meter Pendant							
	3W/3P Advance /Hold Return		4.80	24.15	0.30	700	0.5 Hp
			5.10	48.30	0.61	700	1.0 Hp
			7.80	48.30	1.00	700	1.5 Hp
	4W/3P Advance /Hold/Return		6.3	48	1.22	700	3 Hp
			4.80	24.15	0.30	700	0.5 Hp
			5.10	48.30	0.61	700	1.0 Hp
			7.80	48.30	1.00	700	1.5 Hp
			6.3	48	1.22	700	3 Hp